



misure esterne external size



Video dimostrativo  
Demonstration movie

## C50



C50 forno della serie C ha una Potenza di 2000W, statico, ventilato che lo rendono ideale per ogni cucina. C50 è grado di contenere comodamente al suo interno più piatti, garantendo ottime prestazioni di cottura combinate con un basso consumo energetico grazie al rispetto della normativa A 13. Equipaggiato con 3 resistenze in acciaio corazzato, luce interna, timer da 60 minuti, con blocco, e termostato regolabile fino ad un massimo di 230°C, C50 è dotato di 5 funzioni di cottura, con opzione di regolazione solo grill ideale per grigliare alla perfezione carne e pesce, mentre la ventilazione interna consente una cottura uniforme in tempi brevi.

C50 ha un rivestimento antiaderenti, sulle pareti interne, in ceramica che permette una facile pulizia e anche una maggiore igiene.

C50 è dotato anche di girarrosto per deliziosi polli allo spiedo.

Il vetro è termoisolante e di nuova generazione

La fine cottura viene segnalata tramite segnale acustico e luminoso; il termostato regolabile da 100°C a 230°C, permette di cuocere alla perfezione ogni tipo di piatto, combinando anche le diverse funzioni di cottura: base, grill, combinata e ventilata.

Accessori 1 griglia, 1 leccarda, 1 maniglia di presa leccarda e 1 spiedo.



C50 oven of Series C, it has a 2000W power, static, ventilated, is ideal for any kitchen. C50 is able to comfortably hold within it more dishes, cooking, guaranteeing excellent performance combined with low power consumption due to compliance with regulations A 13. Equipped with 3 resistors in armored steel, interior light, timer 60 minutes, with lock, and adjustable thermostat up to a maximum of 230°C, C50 is equipped with 5 cooking functions, with adjustment option only ideal grill for grilling perfectly meat and fish, while the internal ventilation ensures in a short time cooking.

The glass is heat insulating and new generation.

C50 has a non-stick coating, on the inside walls, in ceramic that allows easy cleaning and even greater hygiene.

C50 is also equipped with a rotisserie for delicious grilled chicken.

The end of cooking is indicated by acoustic and light signal; the thermostat from 100°C to 230°C allows you to cook perfectly every kind of dish, also combining the different functions of cooking: basic, grill, combined and ventilated.

Accessories 1 grid, 1 drip pan, 1 handle grip and 1 rotisserie.



8 008523 011826

GIFT BOX		MASTER CARTON			PALLET	CONTAINER		
Size (mm)	Kg	Pize (mm)	Pcs	Kg	Pcs	20	40	40HQ
640 x 505 x 435	10.5	640 x 505 x 435	1	10.5	16	194	388	481



# SCHEDA PRODOTTO PRODUCT DETAILS

## C50

FAMILY	KITCHEN
CODE	C50
EAN CODE	8008523011826

### CARATTERISTICHE

Potenza 2000 W  
 Statico e ventilato  
 Illuminazione interna  
 Girarrosto  
 Griglia  
 Maniglia termoisolata  
 Teglia con impugnatura removibile  
 Sportello con doppi vetri e pareti termoisolate  
 Regolatore della temperatura da 100°C a 230°C  
 Selettore fonti di calore per differenti modalità di cottura  
 Timer 0-60 min. con indicatore luminoso e sonoro  
 Rivestimento ceramico interno  
 Conforme alla normativa A 13  
 Colore: nero  
 Alimentazione 220 240V~ 50-60 Hz

Dimensioni prodotto esterno: 570 x 450 x 345 mm  
 Dimensioni prodotto interno: 420 x 372 x 297 mm  
 Dimensioni imballo: 640 x 505 x 435 mm  
 Peso imballo + prodotto: 10.5 Kg  
 Pezzi x master: 1 pz  
 Dimensioni master: 640 x 505 x 435 mm  
 Peso master: 10.5 Kg  
 Pezzi x pallet: 16  
 Colli x strato: 4  
 Strati: 4  
 Altezza pallet: 230 cm  
 Peso pallet: 215 Kg  
 container 20: 194 pz  
 Container 40: 388 pz  
 Container 40 HQ : 481 pz  
 Codice certificazione: KMO48LI-AAE

### FEATURES

Power 2000 W.  
 Static and ventilated  
 Interior lighting  
 Rotisserie  
 Grid  
 Heat-insulated handle  
 Baking tray with removable handle  
 Door with double glazing and heat-insulated walls  
 Temperature regulator from 100 ° C to 230 ° C  
 Heat source selector for different cooking modes  
 Timer 0-60 min. with indicator light and sound  
 Internal ceramic coating  
 Compliant with regulation A 13  
 Colour: black  
 Power supply 220 240V ~ 50-60 Hz

External size: 570 x 450 x 345 mm  
 Internal size: 420 x 372 x 297 mm  
 Package dimensions: 640 x 505 x 435 mm  
 Packaging weight + product: 10.5 Kg  
 Master pieces: 1 pc  
 Master size: 640 x 505 x 435 mm  
 Master Weight: 10.5 Kg  
 Pieces for pallet: 16  
 Master for layer: 4  
 Layers: 4  
 Height pallet: 230 cm  
 Weight pallet: 215 Kg  
 Container 20: 194 pcs  
 Container 40: 388 pcs  
 Container 40 HQ: 481 pcs  
 Certification Code: KMO48LI-AAE

