



Video dimostrativo
Demonstration movie

KAMINO



La stufa infrarossi a gas KAMINO di JOHNSON Elettrodomestici con elementi in ceramica è la soluzione ideale per riscaldare grandi ambienti in poco tempo, fino a 120 m², garantendo elevati standard di sicurezza nella gestione del gas.

I due sistemi di sicurezza spengono la stufa se vengono rilevate percentuali di anidride carbonica troppo elevate (>1.5%) e se la fiamma si spegne accidentalmente.

I 3 livelli di potenza garantiscono la massima versatilità di utilizzo.

La solida struttura verniciata, con rotelle alla base può contenere una bombola di GPL da 15kg e la rende facile da spostare da un ambiente ad un altro.

Il regolatore del gas è interamente costruito in Italia in modo da assicurare la massima sicurezza durante il funzionamento.



The KAMINO infrared gas heater by JOHNSON Elettrodomestici with ceramic elements is the ideal solution to heat large rooms in a short time, up to 120 m², guaranteeing high safety standards in gas management.

The two safety systems switch off the gas heater if found too high percentage of carbon dioxide (> 1.5%) and if the flame goes out accidentally.

The 3 power levels guarantee maximum versatility of use

The solid painted, with wheels at the base, contains a LPG cylinder 15kg and makes it easy to move from one environment to another.

The gas regulator is constructed entirely in Italy in order to ensure maximum safety during operation.



8 008523 010614

GIFT BOX		MASTER CARTON			PALLET	CONTAINER		
Size (mm)	Kg	Size (mm)	Pcs	Kg	Pcs	20	40	40HQ
450 x 385 x 755	8.8	450 x 385 x 755	1	8.8	18	186	390	540



SCHEMA PRODOTTO PRODUCT DETAILS

KAMINO

FAMILY

HEATING

CODE

KA

COD. EAN

8008523010614

CARATTERISTICHE

Potenza 3 livelli 1500 - 2800 - 4100 W
Superficie riscaldabile: 120 m²
Accensione piezoelettrica
3 piastre ceramica
Consumo: 298 g/h
Bombola 10/15 Kg
Regolatore erogazione gas, con tubo in dotazione
Dispositivo di sicurezza per l'interruzione automatica del gas in caso di spegnimento accidentale
Dispositivo di sicurezza per l'interruzione automatica del gas se l'anidride carbonica nell'ambiente supera l'1,5%
Maniglie per trasporto
Ruote per trasporto
Alimentazione Gas GPL

Dimensioni prodotto:	415 x 370 x 730 mm
Dimensioni imballo:	450 x 385 x 755 mm
Peso imballo + prodotto:	8.8 Kg
Pezzi x master	1 pz
Dimensioni master:	450 x 385 x 755 mm
Peso master:	8.8 Kg
Pezzi x pallet:	18
Colli x strato:	6
Strati:	3
Altezza pallet:	241 cm
Peso pallet:	178 Kg
Container 20:	186 pz
Container 40:	390 pz
Container 40 HQ :	540 pz
Codice certificazione:	PO-E03

FEATURES

Power 3 levels 1500 - 2800 - 4100 W
Heatable area: 120 m²
Piezoelectric ignition
3 ceramic plates
Consumption: 298 g / h
Usable cylinder: capacity 10/15 Kg
Gas supply regulator, with hose supplied
Safety device for automatic gas cut-off in case of accidental shutdown
Safety device for automatic gas interruption if the carbon dioxide in the environment exceeds 1.5%
Carrying handles
Transport wheels
LPG gas supply

Product dimensions:	415 x 370 x 730 mm
Package dimensions:	450 x 385 x 755 mm
Packaging weight + product:	8.8 Kg
Master pieces:	1 pc
Master size:	450 x 385 x 755 mm
Master Weight:	8.8 Kg
Pieces for pallet:	18
Master for layer:	6
Layers:	3
Height pallet:	241 cm
Weight pallet:	178 Kg
Container 20:	186 pcs
Container 40:	390 pcs
Container 40 HQ:	540 pcs
Certification Code:	PO-E03

